

HIGH RES. MINIATURE CAMERA



CT-5132P

MINIATURE CAMERA





Main Features

- Sony 1/3" 960H CCD II
- 700TV Lines (Resolution)
- 3.6mm Lens
- Day & Night
- D-WDR(Wide Dynamic Range)
- 2D DNR(Digital Noise Reduction)
- Built-in OSD Controller



Dimensions



unit : mm

Specifications

Model	CT-5132P
TV System	PAL
Sensor	Sony 1/3" 960H CCD II
Total Pixels	(H)1020 x (V)596
Effective Pixels	(H)976 x (V)582
Synchronization	H/V 15.625/50Hz
Scanning System	2:1 Interlace
Horizontal Resolution	700 TV Lines
Min. Illumination	Color : 0.1Lux , B/W : 0.01Lux@F1.2, 30IRE
Video Output	1.0Vp-p/75ohm Video 0.71Vp-p
S/N	More than 52dB (AGC off)
O.S.D	LENS, AGC, BACK LIGHT(BLC, HLC, D-WDR), 2D-DNR, WHITE BALANCE, DAY & NIGHT MIRROR, SHARPNESS, GAMMA, MONITOR, LSC, MOTION, PRIVACY (MASK1 ~MASK8), LANGUAGE COMMUNICATION, DPC
γ Correction	0.45, 0.55, 0.65, USER
Monitor	CRT, LCD
Electrical Shutter	1/50~1/100,000
Privacy Masking	8 Windows(Polygonal, 8 Colors)
Day & Night	AUTO, COLOR, BW, EXT, EXT2
Motion Detection	ON / OFF
Language	9 Language
White Balance	ATW / MANUAL / PUSH
D-WDR	ON / OFF (WDR LEVEL)
Mirror	ON / OFF
2D-DNR	OFF, LOW, MID, HIGH
LSC	ON / OFF
DPC	AUTO / OFF
Lens	3.6mm Lens
Operating Temperature/Humidity	-20℃ ~60℃ / 30% ~80%
Storage Temperature/Humidity	-30℃ ~60℃ / 20% ~90%
Power(Max.)	DC 12V, 120mA
Dimension(mm)	36(W) x 36(H) x 26.5(L)
Weight	Approx. 0.12kg